

Safety data sheet according to Regulation (EC) No. 1907/2006

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code. Product name. HI93728-0 Nitrate Reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use.

Determination of Nitrate in Water Samples. Restricted to professional use.

1.3. Details of the supplier of the safety data sheet.

	Name. Full address.	Hanna I str. Han	instruments S.R.L. ina Nr 1	
	District and Country.	457260	loc. Nusfalau Romania	(Salaj)
		Tel.	(+40) 260607700	
		Fax.	(+40) 260607700	
	e-mail address of the competent person. responsible for the Safety Data Sheet.	msds@	hanna.ro	
1.	4. Emergency telephone number.			
	For urgent inquiries refer to.	Emerge	ency Number - International: +(1)-703-5	27-3887 - UK, London:

For urgent inquiries refer to.	Emergency Number - International: +(1)-703-527-38
	+(44)-870-8200418 - CHEMTREC 24 hours/365 days

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

lazard classification and indication:		
Carcinogenicity, category 1B	H350	May cause cancer.
Germ cell mutagenicity, category 2	H341	Suspected of causing genetic defects.
Reproductive toxicity, category 2	H361fd	Suspected of damaging fertility. Suspected of damaging
		the unborn child.
Acute toxicity, category 3	H331	Toxic if inhaled.
Specific target organ toxicity - repeated exposure,	H372	Causes damage to organs through prolonged or repeated
category 1		exposure.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, acute toxicity,	H400	Very toxic to aquatic life.
category 1		
Hazardous to the aquatic environment, chronic toxicity,	H411	Toxic to aquatic life with long lasting effects.
category 2		

2.2. Label elements.

ŀ

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



ΕN



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 2 / 13

SECTION 2. Hazards identification. .../>>

CAS. 490-79-9 1≤x<5

207-718-5

EC.

INDEX.

Signal w	ords:	Danger						
Hazard s	statements:							
H350		May cause canc	er.					
H341	6 -1	Suspected of ca	using genetic defects.					
H3011 H331	ra	Toxic if inhaled	maging fertility. Suspected of damaging the unborn child.					
H372		Causes damage	to organs through prolonged or repeated exposure.					
H314		Causes severe s	skin burns and eye damage.					
H317		May cause an al	lergic skin reaction.					
H400		Very toxic to aqu	latic life.					
H411		Restricted to pro	fessional users.					
Precautio	onary statemer	nts:						
P201		Obtain special ir	structions before use.					
P260		Do not breathe o	lust, fume, gas, mist, vapours, spray.					
P280	D361+D353	Wear protective	gloves, protective clothing, eye protection and face protection.					
P305	+P351+P338	IF IN EYES: Rin	se cautiously with water for several minutes. Remove contact lenses, if present and easy to do.					
		Continue rinsing						
P308-	+P311	IF exposed or co	oncerned: Call a POISON CENTER or doctor.					
P310		Immediately call	a POISON CENTER or doctor.					
P391		Collect spillage.						
Conta	ains:	CADMIUM						
		POTASSIUM DI	POTASSIUM DISULFATE					
		SULFANILIC AC	ND					
2.2 Other l	anarda							
2.3. Other r	lazarus.							
On the b	asis of availab	le data, the product	does not contain any PBT or vPvB in percentage greater than 0,1%.					
SECTIO	N 3. Comp	osition/infor	mation on ingredients.					
3.1. Substa	inces.							
Informati	on not relevan	t.						
3.2. Mixture	es.							
Contain	s:							
Identific	ation.	x = Conc. %.	Classification 1272/2008 (CLP).					
POTASS		\TF						
CAS.	7790-62-7	9≤x< 17	Acute Tox. 3 H331, Skin Corr. 1A H314					
EC.	232-216-8							
INDEX.								
SULFAN	IILIC ACID							
CAS.	121-57-3	1≤x< 5	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317					
EC.	204-482-5							
INDEX.	612-014-00-2	X						
CADMIU	7440 40 0	054445	Core 40 11250 Muto 211244 Done 21126464 Acute Tev 211220 CTOT DE 411070					
CAS.	/440-43-9	$2,5 \le x \le 5$	Carc. 1B H350, Muta. 2 H341, Repr. 2 H361td, Acute Tox. 2 H330, STOT RE 1 H372, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=1					
EC.	231-152-8	0						
2,3-0101								

Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335



Hanna Instruments S.R.L.

HI93728-0 - Nitrate Reagent

Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 3 / 13

SECTION 3. Composition/information on ingredients.

COPPER (II) SULFATE

CAS. 7758-99-8 0,025 ≤ x < 0,25

Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10

EC. 231-847-6 INDEX. 029-004-00-0

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

POTASSIUM DISULFATE

Irritation and corrosion, Cough, Shortness of breath. Risk of blindness!.

SULFANILIC ACID

Irritant effects, Allergic reactions. The following applies to aromatic amines in general: systemic effect: methaemoglobinaemia with headache, cardiac dysrhythmia, drop in blood pressure, dyspnoea, and spasms, principal symptom: cyanosis (blue discolouration of the blood).

CADMIUM

Irritant effects, Cough, Shortness of breath, Diarrhoea, Nausea, Vomiting, Salivation, metallic taste. COPPER (II) SULFATE Irritant effects, conjunctivitis, gastric pain, Diarrhoea, Vomiting, collapse, death Risk of corneal clouding.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

POTASSIUM DISULFATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

SULFANILIC ACID

Combustible. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: Sulphur oxides, nitrogen oxides.

COPPER (II) SULFATE

Not combustible. Ambient fire may liberate hazardous vapours.Fire may cause evolution of: Sulphur oxides.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product and place it in containers for recovery or disposal. If the product is flammable, use explosion-proof equipment. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1A

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

Duadiated was affect as was whether DNEC

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ROU	România	Monitorul Oficial al României 44; 2012-01-19
	TLV-ACGIH	ACGIH 2016

POTASSIUM DISULFATE

Fledicled no-enect co	icenti ation	- FNEC.						
Normal value in fresh	n water					0,68	mg/l	
Normal value in mari	0,068	mg/l						
Normal value for free	2,5	mg/kg/						
Normal value for ma	0,25	₫hg/kg/						
Normal value for wat	6,8	¢hg/l						
Normal value of STP	800	mg/l						
Normal value for the terrestrial compartment 0,092								
Health - Derived no-eff	ect level - D	NEL / DMEL					d	
	Effects or	n consumers.			Effects on we	orkers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Inhalation.							0,13 mg/m3	0,13 mg/m3



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 5 / 13

SECTION 8. Exposure controls/personal protection. ... / >>

SULFANILIC ACID

Predicted no-effect con	ncentration	- PNEC.						
Normal value in fresh	n water					0,023	mg/l	
Normal value in marine water							mg/l	
Normal value for wat	0,23	mg/l						
Normal value of STP microorganisms							mg/l	
Health - Derived no-eff	ect level - D	ONEL / DMEL						
	Effects o	n consumers.			Effects on w	orkers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Oral.			VND	1,67 mg/kg bw/d				
Inhalation.			VND	6,67 mg/m3			VND	13,33 mg/m3
Skin.			VND	1,67 mg/kg bw/d			VND	3,33 mg/kg
								bw/d

CADMIUM

Tł	reshold Limit Va	alue.								
	Туре	Country	TWA/8h		STEL/15	min				
			mg/m3	ppm	mg/m3	ppm				
	VLA	ESP	0,01					INHAL.		
	VLA	ESP	0,002					RESP.		
	VLEP	FRA	0,05							
	WEL	GBR	0,025							
	TLV	ROU	0,05							
	TLV-ACGIH		0,01							
Pr	edicted no-effec	t concentra	tion - PNE	C.						
	Normal value in	fresh water						0,00019	mg/l	
	Normal value in	marine wate	er					0,0014	mg/l	
	Normal value for	r fresh water	sediment					1,8	mg/kg/	
	Normal value for	r marine wat	er sedimen	t				0,64	c hg/kg/	
	Normal value of	STP microo	rganisms					0,02	¢hg/l	
	Normal value for	the terrestri	ial comparti	nent				0,19	mg/kg/	
He	ealth - Derived no	o-effect leve	el - DNEL /	DMEL					d	
		Effec	ts on consu	imers.			Effects on wo	orkers		
	Route of exposu	re Acute	e Acu	te	Chronic	Chronic	Acute local	Acute	Chroni	Chronic
		local	syst	temic	local	systemic		systemic	c local	systemic
	Oral.			,	VND	0,001				
						mg/kg bw/d				
	Inhalation.								0,004	VND
									mg/m3	



SECTION 8. Exposure controls/personal protection./>

COPPER (II) SULFATE

Threshold Limit	Value.				()		
Туре	Country	TWA/8h		STEL/15	min		
,	,	mg/m3	ppm	mg/m3	ppm		
MAK	DEU	0,01		0,02		RESP.	
VLA	ESP	1					
						Copper	
VLEP	FRA	1		2			
						Copper	
WEL	GBR	1		2			
						Copper	
TLV	ROU	0,5		1,5			
						Copper	
TLV-ACGIH		1					
						Copper	
Predicted no-eff	ect concentra	ation - PNE	С.				
Normal value	in fresh water	ſ				0,0078	mg/l
Normal value in marine water						0,0052	mg/l
Normal value for fresh water sediment						87	mg/kg/
Normal value for marine water sediment						676	d hg/kg/
Normal value	of STP micro	organisms				0,23	¢hg/l
Normal value	for the terrest	rial compart	ment			65	mg/kg/
							h

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

CADMIUM

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norm ISO 11174 - Biological Values, ACGIH: 5 µg/g creatinine Cadmium in urine, ESP: 5 µg/g creatinina Cadmio en orina, ROU: 10 µg/g creatinina in urină (sfârșit schimb).

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place. Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374). Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the operator is exposed to a carcinogenic or mutagenic agent, wear a type FFP3 facemask, (see standard EN 149).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 7 / 13

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and cher	nical properties.
Appearance	solid powder
Colour	grey
Odour	odourless
Odour threshold.	Not available.
pH.	2.7 - 3.0 pH, 22 g/L
Melting point / freezing point.	Not available.
Initial boiling point.	Not applicable.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.
Solubility	partially soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
Total solids (250°C / 482°F)	100,00 %
VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

SULFANILIC ACID Decomposes without melting at temperatures > 288°C/550°F.

CADMIUM

Forms explosive mixtures with air on intense heating.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The powders are potentially explosive when mixed with air.

CADMIUM

Risk of ignition or formation of inflammable gases or vapours with: in powder form, with, Air in powder form, with Ammonia nitrile halides. Risk of explosion with: hexafluorobenzene, Hydrazoic acid, ammonium nitrate with heat Zinc, in powder form with Heat Acid, generation of hydrogen). Exothermic reaction with: Alkali metals, chlorates, Strong oxidizing agents, PHOSPHORUS TRICHLORIDE, selenium, in powder form, Tellurium, in powder form.

COPPER (II) SULFATE Exothermic reaction with: Strong oxidizing agents, hydroxylamine, magnesium.

10.4. Conditions to avoid.

Avoid environmental dust build-up.



SECTION 10. Stability and reactivity. .../>>

POTASSIUM DISULFATE Exposure to moisture.

COPPER (II) SULFATE Strong heating (decomposition).

10.5. Incompatible materials.

SULFANILIC ACID

Strong acids and bases. Incompatible with alkyl oxides, aliphatic amines, alcanolamines, amides, ammonia, epichlorohydrin, organic anhydrides, isocyanates, vinyl acetates and oxidising agents.

10.6. Hazardous decomposition products.

SULFANILIC ACID Sulphur oxides, nitric oxides.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

POTASSIUM DISULFATE

Acute inhalation toxicity, absorption, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Lung oedema, Symptoms may be delayed - Skin irritation (in analogy to similar products), Causes severe burns. - Eye irritation (in analogy to similar products), Causes serious eye damage. Risk of blindness!.

SULFANILIC ACID

Acute inhalation toxicity, Symptoms: Possible damages, Irritation symptoms in the respiratory tract - Skin irritation, rabbit, Result: slight irritation, Causes skin irritation - Eye irritation, rabbit, Result: Eye irritation, Causes serious eye irritation - Sensitisation Sensitisation test: guinea pig, Result: positive, May cause an allergic skin reaction.

CADMIUM

Symptoms: mucosal irritations, Cough, Shortness of breath, Inhalation may lead to the formation of oedemas in the respiratory tract. Absorption - CMR effects, Carcinogenicity: May cause cancer - Mutagenicity: Suspected of causing genetic defects - Teratogenicity: Suspected of damaging the unborn child - Reproductive toxicity: Suspected of damaging fertility.

COPPER (II) SULFATE

Skin irritation, Causes skin irritation - Eye irritation, Risk of corneal clouding. conjunctivitis. Causes serious eye irritation - Genotoxicity in vivo, Mutagenicity (mammal cell test): micronucleus, Result: negative (National Toxicology Program) - Genotoxicity in vitro Ames test, Salmonella typhimurium, Result: negative.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component). LC50 (Inhalation - mists / powders) of the mixture: 6,020 mg/l 16000,003 mg/kg LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture: Not classified (no significant component). POTASSIUM DISULFATE 2140 mg/kg Rat LD50 (Oral). 0,85 mg/l/4h Rat LC50 (Inhalation). 2,5-DIHYDROXYBENZOIC ACID LD50 (Oral). 800 mg/kg SULFANILIC ACID LD50 (Oral). > 2000 mg/kg Rat LD50 (Dermal). > 2000 mg/kg Rat

@EPY 9.2.8 - SDS 1003



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 9 / 13

SECTION 11. Toxicological information. ... / >>

CADMIUM LD50 (Oral). LC50 (Inhalation).

COPPER (II) SULFATE LD50 (Oral). LD50 (Dermal). 0,051 mg/l/1h 482 mg/kg Rat

> 2000 mg/kg

890 mg/kg

SKIN CORROSION / IRRITATION. Corrosive for the skin.

SERIOUS EYE DAMAGE / IRRITATION. Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION. Sensitising for the skin.

GERM CELL MUTAGENICITY. Suspected of causing genetic defects.

CARCINOGENICITY. May cause cancer.

REPRODUCTIVE TOXICITY. May damage fertility or the unborn child.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE. Causes damage to organs.

ASPIRATION HAZARD. Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

This product is dangerous for the environment and highly toxic for aquatic organisms. This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity.

CADMIUM Toxicity to bacteria, static test NOEC activated sludge: 0,2 mg/l, 3 h, Analytical monitoring: yes.

POTASSIUM DISULFATE LC50 - for Fish. EC50 - for Crustacea.

SULFANILIC ACID LC50 - for Fish. EC50 - for Crustacea. EC50 - for Algae / Aquatic Plants.

CADMIUM EC50 - for Crustacea. EC50 - for Algae / Aquatic Plants. LC10 for Fish. Chronic NOEC for Algae / Aquatic Plants.

COPPER (II) SULFATE LC50 - for Fish. EC50 - for Crustacea. EC50 - for Algae / Aquatic Plants. Chronic NOEC for Crustacea. 680 mg/l/96h Pimephales promelas 720 mg/l/48h Daphnia magna

> 100 mg/l/96h Danio rerio
23 mg/l/48h Daphnia magna
32 mg/l/72h Desmodesmus subspicatus

0,038 mg/l/48h Daphnia magna 0,0023 mg/l/72h Selenastrum capricornutum 1,5 mg/l/96h Pimephales promelas 0,031 mg/l Scenedesmus guadricauda

0,11 mg/l/96h Oncorhynchus mykiss 0,02 mg/l/48h Daphnia magna 0,02 mg/l/72h 0,0088 mg/l Paracetrotus lividus



SECTION 12. Ecological information. .../>>

ΕN

12.2. Persistence and degradability. SULFANILIC ACID Solubility in water. > 10000 mg/l Rapidly biodegradable. 12.3. Bioaccumulative potential. 2,5-DIHYDROXYBENZOIC ACID Partition coefficient: n-octanol/water. 1,74 SULFANILIC ACID Partition coefficient: n-octanol/water. -2,298 12.4. Mobility in soil. Information not available. 12.5. Results of PBT and vPvB assessment. On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%. 12.6. Other adverse effects. COPPER (II) SULFATE Fungicide. Discharge into the environment must be avoided. **SECTION 13. Disposal considerations.** 13.1. Waste treatment methods. Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations. **SECTION 14. Transport information.** 14.1. UN number. ADR / RID, IMDG, IATA: 2923 14.2. UN proper shipping name.

CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE, CADMIUM,) MIXTURE ADR / RID: IMDG: CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE, CADMIUM,) MIXTURE IATA: CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE, CADMIUM,) MIXTURE

14.3. Transport hazard class(es).

ADR / RID:	Class: 8	Label: 8 (6.1)	
IMDG:	Class: 8	Label: 8 (6.1)	
IATA:	Class: 8	Label: 8 (6.1)	

14.4. Packing group.

ADR / RID, IMDG, IATA: Ш

	Hanna Instrum	Revision nr.1 EN Dated 23/09/2016						
I instruments	HI93728-0 - Nitr	Printed on 24/10/2016 Page n. 11 / 13						
SECTION 14. Transport information/>>								
14.5. Environmental hazards.								
ADR / RID: NC IMDG: NC IATA: NC)))							
14.6. Special precautions f	or user.							
ADR / RID:	HIN - Kemler: 86 Special Provision: -	Limited Quantities: 1 kg	Tunnel restriction code: (E)					
IMDG: IATA:	EMS: F-A, S-B Cargo: Pass.: Special Instructions:	Limited Quantities: 1 kg Maximum quantity: 50 Kg Maximum quantity: 15 Kg A3, A803	Packaging instructions: 863 Packaging instructions: 859					
14.7. Transport in bulk acc	ording to Annex II of Marpol and the IB	C Code.						
Information not relevant.								
SECTION 15. Regul	atory information.							
15.1. Safety, health and en	vironmental regulations/legislation spe	ecific for the substance or mixt	ure.					
Seveso Category - Directiv	e 2012/18/EC: H2-E1							
Restrictions relating to the	product or contained substances pursuant to	Annex XVII to EC Regulation 1907	7/2006.					
Contained substance.	23-28 CADMIUM							
Substances in Candidate I								
	ISI (AII. 39 REACH).							
Substances subject to auth None.	orisarion (Annex XIV REACH).							
Substances subject to expo CADMIUM - (CADMIUM /	ortation reporting pursuant to (EC) Reg. 649/ AND ITS COMPOUNDS)	2012:						
Substances subject to the I None.	Rotterdam Convention:							
Substances subject to the s None.	Stockholm Convention:							
Healthcare controls. Workers exposed to this directive.	s health-dangerous chemical agent mus	st undergo sanitary checks car	ried out in compliance with 2004/37/EC					
WGK 3: Severe hazard to	waters							
15.2. Chemical safety asse	ssment.							
No chemical safety assessment has been processed for the mixture and the substances it contains.								
SECTION 16. Other information.								
Text of hazard (H) indicat	ions mentioned in section 2-3 of the sheet	t:						
Carc. 1BCarcinogenicity, category 1BMuta. 2Germ cell mutagenicity, category 2Repr. 2Reproductive toxicity, category 2Acute Tox. 2Acute toxicity, category 2Acute Tox. 3Acute toxicity, category 3Acute Tox. 4Acute toxicity, category 4STOT RE 1Specific target organ toxicity - repeated exposure, category 1STOT RE 2Specific target organ toxicity - repeated exposure, category 2Skin Corr. 1ASkin corrosion, category 1A								
			@EPY 9.2.8 - SDS 1003					



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 12 / 13

SECTION 16. Other information. ... / >>

Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eve Dam. 1	Serious eve damage, category 1
Eve Irrit. 2	Eve irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H350	May cause cancer.
H341	Suspected of causing genetic defects.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament



Revision nr.1 Dated 23/09/2016 Printed on 24/10/2016 Page n. 13 / 13

SECTION 16. Other information. ... / >>

- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01 / 02 / 03 / 04 / 05 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.