Trafalgar Chemicals - Safety Data Sheet

0549-CH

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.1 Revision date: 16 April 2021
Date printed: 18 September 2025

Section 1. Identification

1.1 Product Identifier 0549-CH

Product Name POTASSIUM PERMANGANATE A.R. 250g.

CAS Number 7722-64-7

REACH Registration No 01-2119480139-34-XXXX

Molecular Formula KMnO =158.03

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Trafalgar Chemicals

TRAFALGAR CHEMICALS

Trafalgar Scientific Ltd. 190 Waterside Road

Leicester Leicestershire LE5 1OZ

UNITED KINGDOM

Phone 0116 2879460

Email info@trafalgarscientific.co.uk Website www.trafalgarscientific.co.uk

1.4 Emergency Telephone (08:00-17:00) +44(0) 116 2879460

(24hr) 112

(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation (EC) 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Oxidising solid, category 2 H272: May intensify fire; oxidizer.

Skin corrosion/irritation, category 1C H314: Causes severe skin burns and eye damage.

Acute toxicity, category 4 (oral) H302: Harmful if swallowed.
Serious eye damage/irritation, category 1 H318: Causes serious eye damage.

Reproductive toxicity, category 2 H361: Suspected of damaging fertility or the unborn child.

Spec target organ tox - repeat, category 2 H373: May cause damage to organs through prolonged or repeated exposure.

Hazard to aquatic environment, category 1 H400: Very toxic to aquatic life.

Hazard to aquatic environment, category 1 H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to regulation (EC) 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Signal word Danger

Hazard Pictograms











Hazard Statements May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage. Very toxic to

aquatic life with long lasting effects. Suspected of damaging fertility or the unborn child. May cause damage to

organs through prolonged or repeated exposure.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Avoid breathing dust / fume / gas / mist /

vapours / spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves / protective clothing / eye protection / face

protection.

Section 3. Composition

3.1 Substances

Component	CAS No.	EC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Potassium permanganate	7722-64-7	231-760-3	01-2119480139-34-XXXX	>99%	Ox. Sol. 2,Skin Corr. 1C,Acute Tox. 4 (O),Eye Dam. 1,Repr. 2,STOT RE 2,Aquatic Acute 1,Aquatic Chronic 1

Section 4. First Aid

4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. If discomfort persists

OBTAIN MEDICAL ATTENTION.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If

discomfort persists OBTAIN MEDICAL ATTENTION.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing stops or shows

signs of failing, apply artificial resuscitation. OBTAIN MEDICAL ATTENTION.

Ingestion If conscious wash out mouth with water. Do NOT induce vomiting. OBTAIN MEDICAL ATTENTION

URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Water spray, foam, dry powder or carbon dioxide.

Unsuitable Media Nothing specified.

5.2 Special hazards arising from the substance or mixture

Hazards Decompose with release of flammable oxygen gas. May produce hazardous fumes if involved in a fire. Potassium

Oxides, Manganese oxides and Formic Acid.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus. Use water spray to keep fire exposed containers cool.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Use approved personal protective equipment. Avoid creating dust. Avoid breathing dust. Ensure adequate

ventilation. Do not allow general use of area until it is safe to do so.

6.2 Environmental precautions

Environmental Stop leak if safe to do so. Keep material out of sewers, storm drains, surface waters and soil. Notify the

Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Wet material with water to make it damp. This will prevent dispersal of the dust during disposal. Shovel/sweep

up into container for removal Wash to drain with copious amounts of water.

Minor Spillage Wash to drain with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath dust. Do not allow to contaminate clothing. Keep away from sources of ignition - No Smoking.

Ensure Local Exhaust Ventilation maintains dust concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in a suitable area for oxidising agents. Keep well separated from acids, metals, explosives, organic peroxides and ignitable materials. Do not store on wooden surfaces.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits					
			Long Term (8hr TWA)		Short Term 15min period)			
Potassium permanganate	7722-64-7	>99%	-	-	-	-		

Exposure data source(s) No occupational exposure data currently available.

8.2 Exposure controls

maintained chemical cartridge respirator, or use self contained breathing apparatus.

Hand Protection Use nitrile gloves or PVC gauntlets.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Dark purple crystalline powder or dark purple crystals with metallic sheen.

Odour Odourless.
pH Not applicable
Boiling Point Not available

Melting Point 240°C (Decomposition)

Flash Point Not applicable
Upper Flammable Limit Not applicable
Lower Flammable Limit Not applicable
Auto Ignition Not applicable

Explosive Properties Not explosive as a single substance.

Oxidising Properties A strong oxidising agent.

Vapour Pressure Not applicable Relative Density 2.7030 Water Solubility 64 g/L

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions but starts to decompose at 240C liberating oxygen.

10.3 Possibility of hazardous No data available.

reactions

Products

10.4 Conditions to Avoid Do not allow to impregnate wood or other organic materials.

10.5 Incompatible materials Reacts explosively with many substances including hydrochloric, sulphuric and acetic acids, formaldehyde, solid

reducing sugars, finely divided metals and organic nitrates. Ignition may occur on contact with dimethyl sulphoxide, glycerol, organic nitro compounds, oxygenated organic compounds especially when mixed with nitric acid. Contact with wood may cause a fire if moist or subject to friction. Violent exotherms have also occurred

with hydrofluoric acid and hydrogen peroxide.

10.6 Hazardous Decomposition Decompose with release of flammable oxygen gas. May produce hazardous fumes if involved in a fire. Potassium

Oxides, Manganese oxides and Formic Acid.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Dilute solutions are mildly irritating to the eye. Concentrated solutions may be irritating to the eyes.

Skin There may be irritation & redness.

LD50 Skin >2000 mg/Kg Rat

Ingestion Harmful if swallowed. Ingestion of low to moderate amounts can result in burning in the throat and gastro-

intestinal effects such as ulceration, nausea, vomiting, diarrhoea and constipation.

LD50 Oral >2000 mg/Kg Rat

Inhalation High concentrations of vapour may produce irritation of the eyes, nose, throat and respiratory tract.

LD50 Inhalation Not available TCLo Not available

Carcinogenicity No information is available.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects Gynaecological disturbances have been reported in women and sexual disfunction in test animals.

Section 12. Ecological

12.1 Toxicity Very Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.

Ref: 0549-CH

LC50 Algal 0.43 mg/L Green algae (72 hours)
LC50 Crustacea 0.06 mg/L Daphnia magna (48 hours)

LC50 Fish 0.47 mg/L Guppy (Poecillia reticulate) (96 hours)

12.2 Persistence and degradability No data available.

12.3 Bioaccumulative potential No data available.12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB

assessment

Assessment not required.

12.6 Other adverse effects

None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Do not dispose of as domestic waste. Mix with a reducing agent eg. sodium metabisulphite or thiosulphate or a

ferrous salt. Dilute with water. A sulphite/ferrous salt requires the addition of 2M sulphuric acid to promote rapid

OXIDIZING

AGENT

reduction. Neutralise slurry with soda ash and wash to drain with lots of water.

Contaminated Packaging Wash out containers with water.

Section 14. Transport Information

1490 14.1 UN Number

14.2 Proper Shipping Name Potassium permanganate

14.3 Transport classes

UN classification 5.1 Subsidiary hazard(s) None Transport category 2 ADR Hazard ID 50 **Tunnel Restriction Code** Ε II



See section 12. 14.5 Environment hazards

14.6 Special precautions for

No special precautions required.

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE) as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Oxidising solid, category 2; Skin corrosion/irritation, category 1C; Acute toxicity, category 4 (oral); Serious eye Classification

damage/irritation, category 1; Reproductive toxicity, category 2; Spec target organ tox - repeat, category 2; Hazard to

aquatic environment, category 1; Hazard to aquatic environment, category 1

Signal word Danger

Hazard Pictograms











Hazard Statements H272, H302, H314+H318, H410, H361, H373

> May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage. Very toxic to aquatic life with long lasting effects. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

P210, P261, P264, P270, P271, P280 **Precautionary Statements**

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Avoid breathing dust / fume / gas / mist / vapours / spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves / protective clothing / eye protection / face

protection.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.1 (Supercedes revision 2.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 18 September 2025

Copyright: 2025 Trafalgar Chemicals